

## IR.EVENT\_DESCRIPTOR\_READ

the identifier of the event that the descriptor was read

### Syntax

```
IR.AddListener(IR.EVENT_DESCRIPTOR_READ, driver, function, [pointer]);
```

<b>input</b>	<b>sample</b>	<b>description</b>
driver	IR.CreateDevice(IR.DEVICE_BLE_DEVICE)	type: object the reference to the driver
function	function() {}	type: function the unnamed function or reference to the function
pointer	-	type: object the pointer to the object which serves the function (optional)
<b>output</b>		
in_ServiceUuid		type: String the service identifier
in_CharacteristicUuid		type: String the identifier of the characteristic
in_uuid		type: String the descriptor identifier
in_data		type: Data the array of bytes - the descriptor value
in_status	0	type: Number 0 - successful or not (another code - error code)

### Example:

```
var device = IR.CreateDevice(IR.DEVICE_BLE_DEVICE)
IR.AddListener(IR.EVENT_DESCRIPTOR_READ, device, function(in_ServiceUuid,
in_CharacteristicUuid, in_uuid, in_data, in_status) {
IR.Log(in_ServiceUuid + " " + in_CharacteristicUuid + " " + in_uuid + " " +
in_data + " " + in_status);
})
```